

SmartReader



Pressure

PRODUCT	FEATURES/DESCRIPTIONS	RANGE	LENGTH/SIZE	COMPATIBILITY	MODEL	CAT. NO.
SmartReader 4 Pressure Modules	1 Plug-in pressure modules for any SmartReader 4 Data Logger (not compatible with SmartReader Plus Model 4). Available in Absolute and Gauge. Comes with a quick release pressure hose connector (not Shown).	0-5 PSI Gauge 0-30 PSI Gauge 0-100 PSI Gauge 0-150 PSI Gauge 0-30 PSI Absolute 0-100 PSI Absolute	na	SR4	PM-005-G PM-030-G PM-100-G PM-150-G PM-030-A PM-100-A	01-0045 01-0047 01-0049 01-0086 01-0046 01-0048
1/4" Pressure Hose	2 Connects to most SmartReader or SmartReader Plus pressure sensors/modules.	0 to 75 PSI -15 to 60°C (4 to 140°F)	OD-6.35 mm (0.25") ID-4.24 mm (0.167")	SR4, SRP4 up to 100 PSI	PH-025-075	30-0004
1/4" Pressure Hose – High Pressure	2 Connects to most SmartReader or SmartReader Plus pressure sensors/modules.	0 to 150 PSI -15 to 60°C (-4 to 140°F)	OD-6.35 mm (0.25") ID-3.0 mm (0.12")	SRP4 150 PSI PM-150G	PH-025-150	30-0006

Other Sensors



PRODUCT	FEATURES/DESCRIPTIONS	RANGE	LENGTH/SIZE	COMPATIBILITY	MODEL	CAT. NO.
Occupancy Detector	1 Detect if a room is occupied and log it with no tools or wiring. The sensor is self powered with a user replaceable battery. Plugs directly into ACR Process Signal Data Loggers. Used in energy management studies and security situations.	0 to 10 meters (30 feet)	30 cm (12")	SR7, SRP7, OWL 400	OC-DET-100	01-0100