

# ▶ PowerPro 100 XNP4 4-Mode Surge Protection Device



## ▶ FEATURES AND BENEFITS

- Provides 100,000 Amp per mode single-pulse surge current capacity (100,000 amps per phase)
- Protects facilities and equipment against the harmful effects of lightning strikes and internally generated electrical transients and noise
- Fulfills the single-pulse surge current capacity testing recommended per NEMA LS-1 2.2.9 and 3.9
- Includes pre-wired pigtail conductors to streamline installation
- Reinforced copper bus design on PCB to minimize system impedances, reducing clamping voltage and increasing reliability
- 10-Year Warranty

## ▶ OPTIONS

- **-45dB EMI Filter:** F to end of model number
- **Remote Dry Contacts:** Form "C" dry contacts for remote alarm monitoring are available as an option. To order a model with Remote alarm option, add -R to end of Model number.
- **Mounting Options:** The Power Pro can be ordered with several mounting options, that determines where the electrical conduit nipple is mounted. Bottom Side is standard, -TS Top Side; -LS Left Side; -RS Right Side

## ▶ APPLICABLE APPROVAL AND STANDARDS

- ETL listed to UL 1449 3rd Edition Sept 2009
- Designed & tested to UL1283
- NEMA LS-1
- ANSI / IEEE C62.1, C62.45, C62.11, C62.41

## ▶ 4-MODE POWER PRO 100 MODEL NUMBERS

Model No.	System Voltage	Service Configuration
XNP4-100-120-1G	120 VAC	1 PHASE, 2 WIRE, W/GROUND
XNP4-100-240-1G	240 VAC	1 PHASE, 2 WIRE, W/GROUND
XNP4-100-120/240-2G	120/240 VAC	1 PHASE, 3 WIRE SPLIT PHASE, W/GROUND
XNP4-100-120/208-3GY	120/208 VAC	3 PHASE, 4 WIRE WYE, W/GROUND
XNP4-100-220/380-3GY	220/380 VAC	3 PHASE, 4 WIRE WYE, W/GROUND
XNP4-100-277/480-3GY	277/480 VAC	3 PHASE, 4 WIRE WYE, W/GROUND
XNP4-100-120/240-3GH	120/240 VAC B PHASE IS 208V	3 PHASE, HIGH-LEG DELTA, W/GROUND
XNP4-100-240-3DG	240VAC	3 PHASE, 3 WIRE DELTA, W/GROUND
XNP4-100-380-3DG	380 VAC	3 PHASE, 3 WIRE DELTA, W/GROUND
XNP4-100-480-3DG	480 VAC	3 PHASE, 3 WIRE DELTA, W/GROUND

\* Optional Feature Codes    -F EMI Filter    -R Remote Alarm

XNP4-100-020911



# ► PowerPro 100 XNP4 4-Mode Surge Protection Device

## TECHNICAL INFORMATION

### ► SURGE VOLTAGE RATING (6 KV / 3000 A COMBINATION WAVEFORM) - UL1449 4TH EDITION

Model No.	System Voltage	MCOV	L-N	L-G	N-G	L-L
XNP4-100-120-1G	120 VAC	150	700	1200	700	1200
XNP4-100-240-1G	240 VAC	320	1000	2000	1000	2000
XNP4-100-120/240-2G	120/240 VAC	150	700	1200	700	1200
XNP4-100-120/208-3GY	120/208 VAC	150	700	1200	700	1200
XNP4-100-220/380-3GY	220/380 VAC	320	1000	2000	1000	2000
XNP4-100-277/480-3GY	277/480 VAC	320	1000	2000	1000	2000
XNP4-100-120/240-3GH	120/240 VAC High Leg	150/320	700/1000	1200	700	1200
XNP4-100-240-3DG	240VAC	320	-	1000	-	2000
XNP4-100-380-3DG	380 VAC	625	-	1600	-	3200
XNP4-100-480-3DG	480 VAC	625	-	1600	-	3200

### ► EMI /RFI NOISE REJECTION

Filtering Attenuation Frequencies (L-N) with 6" Hook Up Wire

Frequency	Noise Source (in dB)
	50 ft.
1 kHz	-1.26
5 kHz	-11.3
10 kHz	-16.47
50 kHz	-31.18
100 kHz	-35.59
150 kHz	-38.41
200 kHz	-40.91
250 kHz	-41.63
500 kHz	-49.49
1 MHz	-43.24

### ► SINGLE-PULSE SURGE CURRENT CAPACITIES


Protection Mode	Single-Pulse Surge Current per Mode
L-N	100,000
L-G	100,000
N-G	100,000
L-L	100,000
Per Phase	100,000

### ► MECHANICAL SPECIFICATIONS

Dimensions	7.39" H x 5.43" W x 4.75" D
Weight	6.5 lbs.
Enclosure Type	NEMA 4X FRP, Non-Removable Cover
Standard Hub Type	3/4" – Rigid or IMC Conduit Optional Stainless Steel Hub Available
Operating Environment	-40C to +60C 5% to 95% humidity

### ► ELECTRICAL SPECIFICATIONS

Connection Method	Parallel
Protection Modes (4 discrete modes)	L-N, L-G, N-G, L-L
Pre-Wired	30" stranded #10 AWG
Status Indicator	LED's for each phase NO/NC Remote Relay Option



Mounting

Overall

E x F  
6.75 x 2

H x W x D  
7.50 x 5.43 x 4.75

SHIPPING SPECS: 8 lbs Standard Box 8" x 6" x 6"